



Trail Uses



No Bikes



Dogs



Equestrian



Hiking



No Motorized Vehicles

Hazards and Obstructions



Noxious Plants
48 inches

Towhee Trail

Anthony Chabot

Trail Length 1.0 mi (1.7 km)

Network trail

If you happen to be camping in the Anthony Chabot park and would like a nice peaceful trail to hike then this is the trail for you. While hiking a long behind the campsites you will run in to friendly turkeys, and birds, and see beautiful views of the surrounding hills.

Cumulative Gain 255 ft (78 m)
Elevation Change Loss 284 ft (87 m)



Typical Grade is 10.0%

24% of the trail is between 16% and 28%
0 ft (0 m) is between 30% and 28%
8% grade is a standard ramp.



Typical Cross Slope is 5.4%

6% of the trail is between 12% and 20%
58 ft (18 m) is between 16% and 20%



Typical Tread Width is 53 in (135 cm)

Tread Width ranges from 32 in (81 cm) to 156 in (396 cm)
Minimum Clearance 44 in (111 cm)



Trail Surface is Soil

74% of the trail is Firm or better
1394 ft (425 m) of the trail is Soft or worse

Trailhead Location

This trail begins along Marciel road among the campsites, after passing through the kiosk, on your right hand side.



Trail Access Information

Warning: Trail conditions may have changed since this trail was assessed. Temporary obstructions (e.g. fallen trees or land slides) may not have been mapped. Maximum grades and cross slopes may vary.

Obstructions less than 6.0 in (15 cm) or outside the tread area 60 in (1.5 m) wide by 96 in (2.4 m) high were not measured. Minimum clearance boundaries were at least 60 in (1.5 m) high.

This report has been generated by TrailWare which has been created by Beneficial Designs, Inc.

Towhee Trail

Length 1.0 mi (1.7 km)

Network trail



No Bikes



Dogs



Equestrian



Typical Grade 10.0%

24% of the trail is

16% to 28%

0 ft (0 m) is 30% to 28 %
8% grade is a standard ramp.



Typical Cross Slope 5.4%

6% of the trail is

12% to 20%

58 ft (18 m) is 16% to 20%



Typical Tread Width

53 in (135 cm)

Minimum 32 in (81 cm)

Maximum 156 in (396 cm)

Minimum Clearance 44 in (111 cm)



Soil

74% is Firm or better

1394 ft (425 m) is Soft or worse



Noxious Plants 48 inches



**Trail Access
Information**



Warning: Trail conditions may have changed since this trail was assessed. Temporary obstructions (e.g. fallen trees or landslides) may not have been mapped. Maximum grades and cross slopes may vary.

This report is generated by TrailWare which has been created by Beneficial Designs Inc.

Aug 26, 05

Towhee Trail

Anthony Chabot

Trail Access Information Summary

Trail Length 1.0 mi (1.7 km)

Network trail

First Segment Assessed

page 1

Aug 12, 05

Last Segment Assessed

Aug 12, 05

Cumulative Elevation Change

Gain 255 ft (78 m)

Loss 284 ft (87 m)

Typical Grade is 10.0%

24% of the trail is between 16% and 28%

0 ft (0 m) is between 30% and 28%

8% grade is a standard ramp.

Locations and lengths can be found on the Maximum Grade Table Reports

Typical Cross Slope is 5.4%

6% of the trail is between 1.2% and 20%

58 ft (18 m) is between 16% and 20%

Locations and lengths can be found on the Maximum X-Slope Table Reports

Typical Tread Width is 53 in (135 cm)

Tread Width ranges from 32 in (81 cm) to 156 in (396 cm)

Minimum Clearance Width is 44 in (111 cm)

Locations and lengths can be found on the Minimum Tread Width Table and Minimum Clearance Width Reports

Trail Surface is Soil

74% of the trail is Firm or better

1394 ft (425 m) of the trail is Soft or worse

Length of trail can be found on the Surface Type Table and Surface Category Table Reports.

Obstructions

Noxious Plants 48 inches

Locations and lengths can be found on the Minimum Vertical and Maximum Tread Obstructions Reports

Trail Uses

No Bikes

Dogs

Equestrian

Warning: Trail conditions may have changed since this trail was assessed. Temporary obstructions (e.g. fallen trees or land slides) may not have been mapped. Maximum grades and cross slopes may vary. Obstructions less than 6.0 in (15 cm) or outside of the tread area 60 in (1.5 m) wide by 96 in (2.4 m) high were not measured. Minimum clearance boundaries were at least 6.0 in (15 cm) high.