



### Trail Uses



Dogs



Hiking



No Motorized Vehicles



Dogs



No Bikes

### Hazards and Obstructions



Roots  
9 in.



Rocks  
6 in.

## Fishing Lake Trail

Don Castro

### Trail Length 0.6 mi (0.9 km)

#### Linear trail

If you love to fish than this is the trail for you. Running right along Fishing Lake, there are many nice and peaceful spots to stop and fish for the day. If you are looking for a midday hike then hop onto the Fishing Lake Trail for a quick stroll to clear your mind.

Cumulative Gain 106 ft (32 m)

Elevation Change Loss 105 ft (32 m)



#### Typical Grade is 6.9%

22% of the trail is between 10% and 29%

485 ft (148 m) is between 14% and 29%

8% grade is a standard ramp.



#### Typical Cross Slope is 5.0%

18% of the trail is between 8% and 30%

220 ft (67 m) is between 12% and 30%



#### Typical Tread Width is 48 in (121 cm)

Tread Width ranges from 16 in (41 cm) to 94 in (239 cm)

Minimum Clearance 20 in (51 cm)



#### Trail Surface is soil

99% of the trail is Firm or better

16 ft (5 m) of the trail is Soft or worse

#### Trailhead Location

This trailhead starts off of Woodroe Ave just before crossing over the stream.



### Trail Access Information

Warning: Trail conditions may have changed since this trail was assessed. Temporary obstructions (e.g. fallen trees or landslides) may not have been mapped. Maximum grades and cross slopes may vary.

Obstructions less than 3.0 in (7.5 cm) or outside the tread area 60 in (1.5 m) wide by 120 in (3 m) high were not measured. Minimum clearance boundaries were at least 30 in (7.5 cm) high.

This report has been generated by TrailWare which has been created by Beneficial Designs, Inc.

# Fishing Lake Trail

Length 0.6 mi (0.9 km)

Linear trail



Dogs



Hiking



No Motorized Vehicles



Typical Grade 6.9%

22% of the trail is

10% to 29%

485 ft (148 m) is 14% to 29%  
8% grade is a standard ramp.



Typical Cross Slope 5.0%

18% of the trail is

8% to 30%

220 ft (67 m) is 12% to 30%



Typical Tread Width

48 in (121 cm)

Minimum 16 in (41 cm)

Maximum 94 in (239 cm)

Minimum Clearance 20 in (51 cm)



soil

99% is Firm or better

16 ft (5 m) is Soft or worse

9 in.



Roots

6 in.



Rocks



Trail Access Information



Warning: Trail conditions may have changed since this trail was assessed. Temporary obstructions (e.g. fallen trees or landslides) may not have been mapped. Maximum grades and cross slopes may vary.

This report is generated by TrailWare which has been created by Beneficial Designs Inc.

Aug 26, 05

# Fishing Lake Trail

Don Castro

## Trail Access Information Summary

**Trail Length 0.6 mi (0.9 km)**

### Linear trail

#### Cumulative Elevation Change

Gain 106 ft (32 m)

Loss 105 ft (32 m)

---

#### Typical Grade is 6.9%

22% of the trail is between 10% and 29%

485 ft (148 m) is between 14% and 29%

8% grade is a standard ramp.

Locations and lengths can be found on the Maximum Grade Table Reports

---

#### Typical Cross Slope is 5.0%

18% of the trail is between 8% and 30%

220 ft (67 m) is between 12% and 30%

Locations and lengths can be found on the Maximum X-Slope Table Reports

---

#### Typical Tread Width is 48 in (121 cm)

Tread Width ranges from 16 in (41 cm) to 94 in (239 cm)

#### Minimum Clearance Width is 20 in (51 cm)

Locations and lengths can be found on the Minimum Tread Width Table and Minimum Clearance Width Reports

---

#### Trail Surface is soil

99% of the trail is Firm or better

16 ft (5 m) of the trail is Soft or worse

Length of trail can be found on the Surface Type Table and Surface Category Table Reports.

---

#### Obstructions

Roots 9 in.

Rocks 6 in.

Locations and lengths can be found on the Minimum Vertical and Maximum Tread Obstructions Reports

---

#### Trail Uses

Dogs

Hiking

No Motorized Vehicles

---

Warning: Trail conditions may have changed since this trail was assessed. Temporary obstructions (e.g. fallen trees or landslides) may not have been mapped. Maximum grades and cross slopes may vary. Obstructions less than 3.0 in (7.5 cm) or outside of the tread area are 60 in (1.5 m) wide by 120 in (3 m) high when measured. Minimum clearance boundaries were at least 3.0 in (7.5 cm) high.