



### Trail Uses



Bicycling



Dogs



Equestrian



Hiking



No Motorcycles

## Old Creek Trail

Quarry Lakes

### Trail Length 1.1 mi (1.8 km)

#### Network trail

This trail is a nice relaxing stroll around and through the lakes. With refreshing views of Rainbow Lake, Horseshoe Lake, and Lago Los Osos Lake, you will enjoy wildlife such as jack rabbits, sea gulls, and vultures.

Cumulative Gain 36 ft (11 m)  
Elevation Change Loss 15 ft (4 m)




#### Typical Grade is 0.9%

2% of the trail is between 5% and 9%  
25 ft (8 m) is between 8% and 9%  
8% grade is a standard ramp.



#### Typical Cross Slope is 1.5%

14% of the trail is between 3% and 15%  
825 ft (251 m) is between 3% and 15%



#### Typical Tread Width is 123 in (312 cm)

Tread Width ranges from 97 in (246 cm) to 208 in (528 cm)  
Minimum Clearance 50 in (127 cm)



#### Trail Surface is Aggregate/Gravel

100% of the trail is Firm or better  
0 ft (0 m) of the trail is Soft or worse

#### Trailhead Location

This trail begins at the front entrance kiosk.



### Trail Access Information

Warning: Trail conditions may have changed since this trail was assessed. Temporary obstructions (e.g. fallen trees or landslides) may not have been mapped. Maximum grades and cross slopes may vary.

Obstructions less than 2.0 in (5.0 cm) or outside the tread area 120 in (3 m) wide by 120 in (3 m) high were not measured. Minimum clearance boundaries were at least 20 in (50 cm) high.

This report has been generated by TrailWare which has been created by Beneficial Designs, Inc.

# Old Creek Trail

---

Length 1.1 mi (1.8 km)

Network trail

---



Bicycling



Dogs



Equestrian

---



Typical Grade 0.9%

---

2% of the trail is

5% to 9%

---

25 ft (8 m) is 8% to 9%  
8% grade is a standard ramp.

---



Typical Cross Slope 1.5%

---

14% of the trail is

3% to 15%

---

825 ft (251 m) is 3% to 15%

---



Typical Tread Width

123 in (312 cm)

---

Minimum 97 in (246 cm)

Maximum 208 in (528 cm)

Minimum Clearance 50 in (127 cm)

---



Aggregate/Gravel

---

100% is Firm or better

---

0 ft (0 m) is Soft or worse

---



Trail Access  
Information



Warning: Trail conditions may have changed since this trail was assessed. Temporary obstructions (e.g. fallen trees or landslides) may not have been mapped. Maximum grades and cross slopes may vary.

This report is generated by TrailWare which has been created by Beneficial Designs Inc.

Aug 26, 05

**Old Creek Trail**  
**Quarry Lakes**  
**Trail Access Information Summary**  
**Trail Length 1.1 mi (1.8 km)**  
**Network trail**

First Segment Assessed Aug 18, 05  
Last Segment Assessed Aug 18, 05

page 1

**Cumulative Elevation Change**

Gain 36 ft (11 m)

Loss 15 ft (4 m)

---

**Typical Grade is 0.9%**

2% of the trail is between 5% and 9%

25 ft (8 m) is between 8% and 9%

8% grade is a standard ramp.

Locations and lengths can be found on the Maximum Grade Table Reports

---

**Typical Cross Slope is 1.5%**

14% of the trail is between 3% and 15%

825 ft (251 m) is between 3% and 15%

Locations and lengths can be found on the Maximum X-Slope Table Reports

---

**Typical Tread Width is 123 in (312 cm)**

Tread Width ranges from 97 in (246 cm) to 208 in (528 cm)

**Minimum Clearance Width is 50 in (127 cm)**

Locations and lengths can be found on the Minimum Tread Width Table and Minimum Clearance Width Reports

---

**Trail Surface is Aggregate/Gravel**

100% of the trail is Firm or better

0 ft (0 m) of the trail is Soft or worse

Length of trail can be found on the Surface Type Table and Surface Category Table Reports.

---

**Obstructions**

Locations and lengths can be found on the Minimum Vertical and Maximum Tread Obstructions Reports

---

**Trail Uses**

Bicycling

Dogs

Equestrian

---

Warning: Trail conditions may have changed since this trail was assessed. Temporary obstructions (e.g. fallen trees or landslides) may not have been mapped. Maximum grades and cross slopes may vary. Obstructions less than 2.0 in (5.0 cm) or outside of the tread area a 120 in (3 m) wide by 120 in (3 m) high were not measured. Minimum clearance boundaries were at least 2.0 in (5.0 cm) high.