



**Trail Uses**



Hiking



Bicycling



Dogs

# Killdeer/ Duck Pond Loop Trail

Radke Martinez Regional Shoreline

## Trail Length 0.9 mi (1.5 km)

### Network trail

This trail starts in an accessible parking lot and leads out to the bay. It has beautiful views of the bay on one side and a duck pond on the other. This trail has easy grades throughout and would be a good trail for users of all ability levels.

**Cumulative Gain** 24 ft (7 m)  
**Elevation Change Loss** 17 ft (5 m)



### Typical Grade is 0.8%

4% of the trail is between 3% and 13%  
217 ft (66 m) is between 3% and 13%  
8% grade is a standard ramp.



### Typical Cross Slope is 7.9%

7% of the trail is between 5% and 30%  
350 ft (107 m) is between 5% and 30%



### Typical Tread Width is 103 in (262 cm)

Tread Width ranges from 44 in (112 cm) to 215 in (546 cm)



### Trail Surface is Aggregate/Gravel

94% of the trail is Firm or better  
299 ft (91 m) of the trail is Soft or worse

### Trailhead Location

This trail begins at the parking lot at the intersection of Ferry St. and Joe Dimaggio Dr.



### Trail Access Information

Warning: Trail conditions may have changed since this trail was assessed. Temporary obstructions (e.g. fallen trees or landslides) may not have been mapped. Maximum grades and cross slopes may vary.

Obstructions less than 2.0 in (5.0 cm) or outside the tread area will be by 120 in (3 m) high were not measured. Minimum clearance boundaries were at least 20 in (50 cm) high.

This report has been generated by TrailWare which has been created by Beneficial Designs, Inc.

# Killdeer/ Duck Pond Loop Trail

---

Length 0.9 mi (1.5 km)

Network trail

---



Hiking



Bicycling



Dogs

---



Typical Grade 0.8%

---

4% of the trail is

3% to 13%

---

217 ft (66 m) is 3% to 13%  
8% grade is a standard ramp.

---



Typical Cross Slope 7.9%

---

7% of the trail is

5% to 301%

---

350 ft (107 m) is 5% to 301%

---



Typical Tread Width

103 in (262 cm)

---

Minimum 44 in (112 cm)

Maximum 215 in (546 cm)

---



Aggregate/Gravel

---

94% is Firm or better

---

299 ft (91 m) is Soft or worse

---



Trail Access  
Information



Warning: Trail conditions may have changed since this trail was assessed. Temporary obstructions (e.g. fallen trees or landslides) may not have been mapped. Maximum grades and cross slopes may vary.

This report is generated by TrailWare which has been created by Beneficial Designs Inc.

Aug 26, 05

**Killdeer/ Duck Pond Loop  
Trail**  
**Radke Martinez Regional Shoreline  
Trail Access Information Summary**  
**Trail Length 0.9 mi (1.5 km)**  
**Network trail**

First Segment Assessed

page 1

Jul 18, 05

Last Segment Assessed

Jul 18, 05

**Cumulative Elevation Change**

Gain 24 ft (7 m)

Loss 17 ft (5 m)

**Typical Grade is 0.8%**

4% of the trail is between 3% and 13%

217 ft (66 m) is between 3% and 13%

8% grade is a standard ramp.

Locations and lengths can be found on the Maximum Grade Table Reports

**Typical Cross Slope is 7.9%**

7% of the trail is between 5% and 301%

350 ft (107 m) is between 5% and 301%

Locations and lengths can be found on the Maximum X-Slope Table Reports

**Typical Tread Width is 103 in (262 cm)**

Tread Width ranges from 44 in (112 cm) to 215 in (546 cm)

Locations and lengths can be found on the Minimum Tread Width Table and Minimum Clearance Width Reports

**Trail Surface is Aggregate/Gravel**

94% of the trail is Firm or better

299 ft (91 m) of the trail is Soft or worse

Length of trail can be found on the Surface Type Table and Surface Category Table Reports.

**Obstructions**

Locations and lengths can be found on the Minimum Vertical and Maximum Tread Obstructions Reports

**Trail Uses**

Hiking

Bicycling

Dogs

Warning: Trail conditions may have changed since this trail was assessed. Temporary obstructions (e.g. fallen trees or landslides) may not have been mapped. Maximum grades and cross slopes may vary. Obstructions less than 2.0 in (5.0 cm) or outside of the tread area are wide by 1.20 in (3 m) high are not measured. Minimum clearance boundaries are at least 2.0 ft (50 cm) high.