



### Trail Uses



Equestrian



Bicycling



Hiking



Dogs



No Motorized Vehicles

### Hazards and Obstructions



Ruts  
10 in.

## Nortonville Trail

Black Diamond

**Trail Length 0.6 mi (0.9 km)**

**Network trail**

This section of Nortonville Trail follows an old wagon road through the town site of Somersville uphill to Rosehill Cemetery. The Cemetery dates to the mid 1800's and is the final resting place for nearly 200 protestant miners and their families.

**Cumulative Gain 281 ft (86 m)**  
**Elevation Change Loss 13 ft (4 m)**



**Typical Grade is 9.5%**

20% of the trail is between 14% and 28%  
116 ft (35 m) is between 20% and 28%  
8% grade is a standard ramp.



**Typical Cross Slope is 6.0%**

9% of the trail is between 12% and 18%  
148 ft (45 m) is between 16% and 18%



**Typical Tread Width is 122 in (311 cm)**

Tread Width ranges from 72 in (183 cm) to 160 in (406 cm)  
Minimum Clearance 21 in (52 cm)



**Trail Surface is Soil**

86% of the trail is Firm or better  
430 ft (131 m) of the trail is Soft or worse

### Trailhead Location

Trail begins at the southern most end of the parking lot at the end of Somersville Road.



### Trail Access Information

Warning: Trail conditions may have changed since this trail was assessed. Temporary obstructions (e.g. fallen trees or land slides) may not have been mapped. Maximum grades and cross slopes may vary.

Obstructions less than 2.0 in (5.0 cm) or outside the tread area 120 in (3 m) wide by 120 in (3 m) high were not measured. Minimum clearance boundaries were at least 2.0 in (5.0 cm) high.

This report has been generated by TrailWare which has been created by Beneficial Designs, Inc.

# Nortonville Trail

---

Length 0.6 mi (0.9 km)

Network trail

---



Equestrian



Bicycling



Hiking

---



Typical Grade 9.5%

---

20% of the trail is  
14% to 28%

---

116 ft (35 m) is 20% to 28%  
8% grade is a standard ramp.

---



Typical Cross Slope 6.0%

---

9% of the trail is  
12% to 18%

---

148 ft (45 m) is 16% to 18%

---



Typical Tread Width  
122 in (311 cm)

---

Minimum 72 in (183 cm)

Maximum 160 in (406 cm)

Minimum Clearance 21 in (52 cm)

---



Soil

---

86% is Firm or better

---

430 ft (131 m) is Soft or worse

---



Ruts 10 in.

---



Trail Access  
Information



Warning: Trail conditions may have changed since this trail was assessed. Temporary obstructions (e.g. fallen trees or land slides) may not have been mapped. Maximum grades and cross slopes may vary.

This report is generated by TrailWare which has been created by Beneficial Designs Inc.

Aug 26, 0

**Nortonville Trail**  
**Black Diamond**  
**Trail Access Information Summary**  
**Trail Length 0.6 mi (0.9 km)**  
**Network trail**

page 1  
First Segment Assessed Jun 17, 05  
Last Segment Assessed Jun 17, 05

**Cumulative Elevation Change**

Gain 281 ft (86 m)  
Loss 13 ft (4 m)

---

**Typical Grade is 9.5%**

20% of the trail is between 14% and 28%  
116 ft (35 m) is between 20% and 28%  
8% grade is a standard ramp.  
Locations and lengths can be found on the Maximum Grade Table Reports

---

**Typical Cross Slope is 6.0%**

9% of the trail is between 12% and 18%  
148 ft (45 m) is between 16% and 18%  
Locations and lengths can be found on the Maximum X-Slope Table Reports

---

**Typical Tread Width is 122 in (311 cm)**

Tread Width ranges from 72 in (183 cm) to 160 in (406 cm)

**Minimum Clearance Width is 21 in (52 cm)**

Locations and lengths can be found on the Minimum Tread Width Table and Minimum Clearance Width Reports

---

**Trail Surface is Soil**

86% of the trail is Firm or better  
430 ft (131 m) of the trail is Soft or worse  
Length of trail can be found on the Surface Type Table and Surface Category Table Reports.

---

**Obstructions**

Ruts 10 in.

Locations and lengths can be found on the Minimum Vertical and Maximum Tread Obstructions Reports

---

**Trail Uses**

Equestrian  
Bicycling  
Hiking

---

Warning: Trail conditions may have changed since this trail was assessed. Temporary obstructions (e.g. fallen trees or land slides) may not have been mapped. Maximum grades and cross slopes may vary. Obstructions less than 2.0 in (5.0 cm) or outside of the tread area 120 in (3 m) wide by 120 in (3 m) high were not measured. Minimum clearance boundaries were at least 2.0 in (5.0 cm) high.