



Trail Uses



Bicycling



Equestrian



Hiking



No Motorized Vehicles

Hazards and Obstructions



Steps
5 in.

Rocky Ridge Trail

Las Trampas

Trail Length 0.5 mi (0.8 km)

Linear trail

This trail is extremely steep however with beautiful views of surrounding cities and hills. You will also enjoy the company of many different types of birds.

Cumulative Gain 475 ft (145 m)
Elevation Change Loss 0 ft (0 m)



Typical Grade is 17.5%

22% of the trail is between 20% and 25%
0 ft (0 m) is between 30% and 25%
8% grade is a standard ramp.



Typical Cross Slope is 2.6%

18% of the trail is between 5% and 12%
100 ft (30 m) is between 10% and 12%



Typical Tread Width is 126 in (321 cm)

Tread Width ranges from 101 in (257 cm) to 160 in (406 cm)



Trail Surface is Asphalt

100% of the trail is Firm or better
0 ft (0 m) of the trail is Soft or worse

Trailhead Location

This trail begins at the Bollinger Canyon main lot.



Trail Access Information

Warning: Trail conditions may have changed since this trail was assessed. Temporary obstructions (e.g. fallen trees or landslides) may not have been mapped. Maximum grades and cross slopes may vary.

Obstructions less than 2.0 in (5.0 cm) or outside the tread area width by 120 in (3 m) high were not measured. Minimum clearance boundaries were at least 60 in (15 cm) high.

This report has been generated by TrailWare which has been created by Beneficial Designs, Inc.

Rocky Ridge Trail

Length 0.5 mi (0.8 km)

Linear trail



Bicycling



Equestrian



Hiking



Typical Grade 17.5%

22% of the trail is

20% to 25%

0 ft (0 m) is 30% to 25 %
8% grade is a standard ramp.



Typical Cross Slope 2.6%

18% of the trail is

5% to 12%

100 ft (30m) is 10% to 12%



Typical Tread Width

126 in (321 cm)

Minimum 101 in (257 cm)

Maximum 160 in (406 cm)



Asphalt

100% is Firm or better

0 ft (0 m) is Softer or worse



Steps 5 in.



Trail Access
Information



Warning: Trail conditions may have changed since this trail was assessed. Temporary obstructions (e.g. fallen trees or landslides) may not have been mapped. Maximum grades and cross slopes may vary.

This report is generated by TrailWare which has been created by Beneficial Designs Inc.

Aug 26, 05

Rocky Ridge Trail
Las Trampas
Trail Access Information Summary
Trail Length 0.5 mi (0.8 km)
Linear trail

First Segment Assessed

page 1

Jul 21, 05

Last Segment Assessed

Jul 21, 05

Cumulative Elevation Change

Gain 475 ft (145 m)

Loss 0 ft (0 m)

Typical Grade is 17.5%

22% of the trail is between 20% and 25%

0 ft (0 m) is between 30% and 25%

8% grade is a standard ramp.

Locations and lengths can be found on the Maximum Grade Table Reports

Typical Cross Slope is 2.6%

18% of the trail is between 5% and 12%

100 ft (30 m) is between 10% and 12%

Locations and lengths can be found on the Maximum X-Slope Table Reports

Typical Tread Width is 126 in (321 cm)

Tread Width ranges from 101 in (257 cm) to 160 in (406 cm)

Locations and lengths can be found on the Minimum Tread Width Table and Minimum Clearance Width Reports

Trail Surface is Asphalt

100% of the trail is Firm or better

0 ft (0 m) of the trail is Soft or worse

Length of trail can be found on the Surface Type Table and Surface Category Table Reports.

Obstructions

Steps 5 in.

Locations and lengths can be found on the Minimum Vertical and Maximum Tread Obstructions Reports

Trail Uses

Bicycling

Equestrian

Hiking

Warning: Trail conditions may have changed since this trail was assessed. Temporary obstructions (e.g., fallen trees or land slides) may not have been mapped. Maximum grades and cross slopes may vary. Obstructions less than 2.0 in (5.0 cm) or outside of the tread area are wide by 1.20 in (3 m) high are not measured. Minimum clearance boundaries are at least 6.0 in (15 cm) high.